

EG60 Specification

EG60 is a 2G&4G Non-rechargeable tracker, equipped with an Ultra-high capacity battery for extended usage and powerful

magnets for concealed installation.

This product supports:

1. 2G&4G Cat.1
2. GNSS: GPS/ GALILEO/ BeiDou/ GLONASS
3. IP67 rating
4. Powerful Magnetic Mount
5. 19000mAh Battery
6. Configurator and FOTA WEB

10 Years, Ultra-high capacity

IP67



Low power:
as low as:8uA

Communication Specifications

Technology	2G&4G Cat. 1
Data Support	SMS (TXT/ PDU)
4G Band	- GSM: 850/ 900/ 1800/ 1900 - STD Band: B1/ B2/ B3/ B5/ B7/ B8/ B20/ B28/ B66(B4)/ B38/ B39/ B34/ B40/ B41(Optional) - NA Band: B2/ B5/ B12/ B17/ B13/66(B4) / B38/ B39/ B34/ B40/ B41(Optional)

GNSS Technical

Technology	GNSS: GPS/ GALILEO/ BeiDou/ GLONASS
Tracking Sensitivity	-165dB
Capture Sensitivity	-159dB
Position Accuracy	<2.0m CEP
Hot Start	<1s
Cold start	<24s

Power Consumption

Power Consumption	@3.6V 8uA (Sleep Mode)
Battery Capacity	3.6V 19000mAh Li-SOCl₂ Battery - High-precision electricity meter, accurate to 0.0001%
Battery Life	~10 years

Features

Working Modes	- Tracking Mode - Clock Mode - Times Mode
Alarm function	- Light Sensor Alert - Low Power Alert
Configuration Support	Configurator, FOTA WEB, SMS, Monitoring Platform

Physical & Interface Specifications

Working Temperature	-25°C to +75°C
Storage Temperature	-40°C to +85°C
Ingress Protection Rating	IP67
LED	- Yellow: Location - Red: Communication
Interface	Micro-SIM, Type-C
Color	Black
Product Dimensions	L 81* W 111* H 42.77 mm
Weight	291g

Regulatory Compliance

Certification	CE,FCC,EMARK,UKCA
Product Name	EG60

Appearance

Unit: mm

